



# PreSolve® Orange Degreaser



## FEATURES

- High performance industrial degreaser that works on contact
- Ideal for removing grease, tars, and oils
- Fast acting, deep penetration
- Controlled evaporation
- Flash point above 100°F (38°C)
- Low residue
- Safe on all metals and most plastics

## APPLICATIONS

- Air Compressors
- Alternators
- Bearings
- Chains & Cable Connections
- Cranes
- Engines
- Fork Lifts
- Gears
- Heavy Equipment
- Power and Air Tools
- Printing Presses
- Pulleys

## SPECIFICATIONS AND APPROVALS

- Airbus SIL 20-006 Rev. 2
- AMS 1525B
- Boise Cascade
- Caterpillar
- Cummins Engine
- Dresser Rand
- Ford Motor Co.
- General Motors Co.
- H01.3086
- Honda Corp.
- Inland Steel
- Kimberly-Clark
- Kodak
- Lockheed Martin DSDN
- McDonnell Douglas CSD #1
- Minntac - US Steel
- MMC 21529
- New York City Transit
- NSF International, C1 - Aerosol
- NSF International, C1 - Non-Aerosol
- Pratt & Whitney Canada
- Tampa Electric Co.
- Timken Steel
- Xerox

## PROPERTIES

<b>Appearance / Physical State</b>	Gas/Aerosol - Liquid/Bulk
<b>Odor</b>	Orange
<b>Melting Point / Freezing Point</b>	Not established
<b>Boiling Point / Range</b>	> 302°F (> 150°C)
<b>Vapor Pressure</b>	< 5 mm Hg @ 20°C
<b>Partition Coefficient</b>	<1
<b>Percent Volatile</b>	100%
<b>Flammability Limit</b>	Flammability limit - lower (%) 0.7% Flammability limit - upper (%) 6%
<b>Propellant</b>	Petroleum Gases, Liquified
<b>VOC Content</b>	(Aerosol) 97.2%, (Bulk) 100% per US State and Federal Consumer Product Regulations CARB
<b>Color</b>	Clear water-white
<b>Flash Point</b>	104.0°F (40.0°C) Tag Closed Cup (dispensed liquid)
<b>Relative Density</b>	Not available
<b>Evaporation Rate</b>	0.2 (BuAc = 1)
<b>Vapor Density</b>	> 1 (air = 1)
<b>Auto-Ignition Temperature</b>	> 392°F (> 200°C)
<b>Viscosity</b>	< 3 cSt
<b>Specific Gravity (water=1)</b>	0.82 - 0.86 @ 20°C
<b>Solubility (water)</b>	< 15%
<b>Temperature Range °F(°C)</b>	Not available
<b>4-Ball Weld Load</b>	Not applicable

## DIRECTIONS

Apply on parts and equipment. Allow solvent to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

## HANDLING

Aerosol - Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. (see Section 7 of the SDS)

## STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. (see Section 7 of the SDS)

## DISPOSAL INFORMATION

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

## AVAILABLE PRODUCTS

US	Part No.		Net Contents	Container Type	Units/Case	Case Weight
	Canada	Europe				
		M01405	20 L	pail	1	
		M01415	5 L	pail	1	
01420	C01420	M01420	15 wt oz / 425 g / 523	aerosol	12	15 lbs
01422	C01422		20 fl oz / 591 mL	trigger	12	
01428	C01428		1 gal / 3.78 L	pail	1	
01405	C01405		5 gal / 18.93 L	pail	1	
01455	C01455		55 gal / 208 L	drum	1	369 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved